

GarageMate. VersaShelf®

Instructions

The simplest way to make the VersaShelf work properly for you is to follow the easy step-by-step instructions. Once you open the box please make sure that all the pieces are enclosed. If you find any discrepancy, call us and we will help you with any questions that you may have. Our toll free number is **888-722-5240**. If you call us on the weekend or after hours please leave a message and we will get back to you promptly. Our time zone is Pacific Coast time.

**Contents: Tool holder shelf-Quantity 1
Four-pocket shelf –Quantity 1
Basic shelf-Quantity 1**

Installation: First decide which application you want to use the shelf in: pegboard, in-between studs (16-inch on center), or flat wall surface.



Flat wall install: Cut off top two extending plastic pins pointing up, with dykes. Hold flush against wall pressing lower pins into dry wall. With shelf perpendicular to wall, insert screws into top hole on the left and top hole on the right. Screw firmly into wall at stud.

Stud Wall install (16-inches on center): Place shelf at desired level in-between studs inserting shelf into space between studs. Shelf will be flush with studs. Screw into studs through hole on the left and right.

Pegboard install: Place shelf at desired level and tilt front of shelf up at 45-degree angle insert top two plastic pins into pegboard, lower shelf to insert lower plastic pins into pegboard.



Heininger Holdings, LLC

2222 Queen Street Bellingham, WA 98229-4753

Phone: 888-722-5240 Fax: (360) 756-2414

www.heininger.biz

Makers of: Advantage® Sports Rack, HitchMate® Cargo Products, DriveGear™ Garments, CommuteMate™ Travel Enhancements & GarageMate Organizational Products